CAMBRIDGE INTERNATIONAL EXAMINATIONS

GCE Advanced Subsidiary Level and GCE Advanced Level

MARK SCHEME for the May/June 2013 series

9702 PHYSICS

9702/41 Paper 4 (A2 Structured Questions), maximum raw mark 100

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2013 series for most IGCSE, GCE Advanced Level and Advanced Subsidiary Level components and some Ordinary Level components.

CAMBRIDGE
International Examinations

Section A

1 (a) region of space area / volume — B1
where a mass experiences a force — B1 [2]

(b) (i) force proportional to product of two masses — M1
force inversely proportional to the square of their separation — M1
either reference to point masses *or* separation >> 'size' of masses — A1 [3]

(ii) field strength = GM / x^2 **or** field strength $\propto 1 / x^2$ — C1
ratio = $(7.78 \times 10^8)^2 / (1.5 \times 10^8)^2$ — C1
= 27 — A1 [3]

(c) (i) *either* centripetal force = $mR\omega^2$ and $\omega = 2\pi / T$
or centripetal force = mv^2 / R and $v = 2\pi R / T$ — B1
gravitational force provides the centripetal force — B1
either $GMm / R^2 = mR\omega^2$ *or* $GMm / R^2 = mv^2 / R$ — M1
$M = 4\pi^2 R^3 / GT^2$ — A0 [3]
(allow working to be given in terms of acceleration)

(ii) $M = \{4\pi^2 \times (1.5 \times 10^{11})^3\} / \{6.67 \times 10^{-11} \times (3.16 \times 10^7)^2\}$ — C1
$= 2.0 \times 10^{30}$ kg — A1 [2]

2 (a) obeys the equation pV = constant $\times T$ or $pV = nRT$ — M1
p, V and T explained — A1
at all values of p, V and T/fixed mass/n is constant — A1 [3]

(b) (i) $3.4 \times 10^5 \times 2.5 \times 10^3 \times 10^{-6} = n \times 8.31 \times 300$ — M1
$n = 0.34$ mol — A0 [1]

(ii) for total mass/amount of gas
$3.9 \times 10^5 \times (2.5 + 1.6) \times 10^3 \times 10^{-6} = (0.34 + 0.20) \times 8.31 \times T$ — C1
$T = 360$ K — A1 [2]

(c) when tap opened
gas passed (from cylinder B) to cylinder A — B1
work done <u>on</u> gas in cylinder A (and no heating) — M1
so internal energy and hence temperature increase — A1 [3]

© Cambridge International Examinations 2013

3 (a) (i) 1. amplitude = 1.7 cm — A1 [1]

2. period = 0.36 cm — C1
frequency = 1/0.36
= 2.8 Hz — A1 [2]

(ii) $a = (-)\omega^2 x$ and $\omega = 2\pi/T$ — C1
acceleration = $(2\pi/0.36)^2 \times 1.7 \times 10^{-2}$ — M1
= 5.2 m s^{-2} — A0 [2]

(b) graph: straight line, through origin, with negative gradient — M1
from $(-1.7 \times 10^{-2}, 5.2)$ to $(1.7 \times 10^{-2}, -5.2)$ — A1 [2]
(if scale not reasonable, do not allow second mark)

(c) *either* kinetic energy = $\frac{1}{2}m\omega^2(x_0^2 - x^2)$
or potential energy = $\frac{1}{2}m\omega^2 x^2$ and potential energy = kinetic energy — B1
$\frac{1}{2}m\omega^2(x_0 - x^2) = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$ or $\frac{1}{2}m\omega^2 x^2 = \frac{1}{2} \times \frac{1}{2}m\omega^2 x_0^2$ — C1
$x_0^2 = 2x^2$
$x = x_0 / \sqrt{2} = 1.7 / \sqrt{2}$
= 1.2 cm — A1 [3]

4 (a) work done moving unit positive charge — M1
from infinity (to the point) — A1 [2]

(b) (gain in) kinetic energy = change in potential energy — B1
$\frac{1}{2}mv^2 = qV$ leading to $v = (2Vq/m)^{\frac{1}{2}}$ — B1 [2]

(c) *either* $(2.5 \times 10^5)^2 = 2 \times V \times 9.58 \times 10^7$ — C1
$V =$ 330 V — M1
this is less than 470 V and so 'no' — A1 [3]

or $v = (2 \times 470 \times 9.58 \times 10^7)$ — (C1)
$v = 3.0 \times 10^5$ m s^{-1} — (M1)
this is greater than 2.5×10^5 m s^{-1} and so 'no' — (A1)

or $(2.5 \times 10^5)^2 = 2 \times 470 \times (q/m)$ — (C1)
$(q/m) = 6.6 \times 10^7$ C kg^{-1} — (M1)
this is less than 9.58×10^7 C kg^{-1} and so 'no' — (A1)

© Cambridge International Examinations 2013

5 **(a)** (uniform magnetic) flux normal to long (straight) wire carrying a current of 1 A — M1
(creates) force per unit length of $1\,N\,m^{-1}$ — A1 [2]

(b) **(i)** flux density $= 4\pi \times 10^{-7} \times 1.5 \times 10^{3} \times 3.5$ — C1
$= 6.6 \times 10^{-3}\,T$ — A1 [2]

(ii) flux linkage $= 6.6 \times 10^{-3} \times 28 \times 10^{-4} \times 160$ — C1
$= 3.0 \times 10^{-3}\,Wb$ — A1 [2]

(c) **(i)** (induced) e.m.f. proportional to rate of — M1
change of (magnetic) flux (linkage) — A1 [2]

(ii) e.m.f. $= (2 \times 3.0 \times 10^{-3}) / 0.80$ — C1
$= 7.4 \times 10^{-3}\,V$ — A1 [2]

6 **(a)** **(i)** to reduce power loss in the core — B1
due to eddy currents/induced currents — B1 [2]

(ii) *either* no power loss in transformer
or input power = output power — B1 [1]

(b) *either* r.m.s. voltage across load $= 9.0 \times (8100 / 300)$ — C1
peak voltage across load $= \sqrt{2} \times 243$
$= 340\,V$ — A1 [2]
or peak voltage across primary coil $= 9.0 \times \sqrt{2}$ — (C1)
peak voltage across load $= 12.7 \times (8100/300)$
$= 340\,V$ — (A1)

7 **(a)** **(i)** lowest frequency of e.m. radiation — M1
giving rise to emission of electrons (from the surface) — A1 [2]

(ii) $E = hf$ — C1
threshold frequency $= (9.0 \times 10^{-19}) / (6.63 \times 10^{-34})$
$= 1.4 \times 10^{15}\,Hz$ — A1 [2]

(b) *either* $300\,nm \equiv 10 \times 10^{15}\,Hz$ (and $600\,nm \equiv 5.0 \times 10^{14}\,Hz$)
or $300\,nm \equiv 6.6 \times 10^{-19}\,J$ (and $600\,nm \equiv 3.3 \times 10^{-19}\,J$)
or zinc $\lambda_0 = 340\,nm$, platinum $\lambda_0 = 220\,nm$ (and sodium $\lambda_0 = 520\,nm$) — M1
emission from sodium and zinc — A1 [2]

(c) each photon has larger energy — M1
fewer photons per unit time — M1
fewer electrons emitted per unit time — A1 [3]

© Cambridge International Examinations 2013

8 **(a)** two (light) nuclei combine M1
to form a more massive nucleus A1 [2]

(b) **(i)** Δm $= (2.01410\,\text{u} + 1.00728\,\text{u}) - 3.01605\,\text{u}$
$= 5.33 \times 10^{-3}\,\text{u}$ C1
energy $= c^2 \times \Delta m$ C1
$= 5.33 \times 10^{-3} \times 1.66 \times 10^{-27} \times (3.00 \times 10^8)^2$
$= 8.0 \times 10^{-13}\,\text{J}$ A1 [3]

(ii) speed/kinetic energy of proton and deuterium must be very large B1
so that the nuclei can overcome electrostatic repulsion B1 [2]

Section B

9 **(a)** **(i)** light-dependent resistor/LDR B1 [1]

(ii) strain gauge B1 [1]

(iii) quartz/piezo-electric crystal B1 [1]

(b) **(i)** resistance of thermistor decreases as temperature increses M1
etiher $V_{OUT} = V \times R / (R + R_T)$
or current increases and $V_{OUT} = I R$ A1
V_{OUT} increases A1 [3]

(ii) *either* change in R_T with temperature is non-linear
or V_{OUT} is not proportional to R_T/ change in V_{OUT} with R_T is non-linear M1
so change is non-linear A1 [2]

10 **(a)** sharpness: how well the edges (of structures) are defined B1
contrast: difference in (degree of) blackening between structures B1 [2]

(b) e.g. scattering of photos in tissue/no use of a collimator/no use of lead grid
large penumbra on shadow/large area anode/wide beam
large pixel size
(any two sensible suggestions, 1 each) B2 [2]

(c) **(i)** $I = I_0 e^{-\mu x}$ C1
ratio $= \exp(-2.85 \times 3.5) / \exp(-0.95 \times 8.0)$ C1
$= (4.65 \times 10^{-5}) / (5.00 \times 10^{-4})$
$= 0.093$ A1 [3]

(ii) *either* large difference (in intensities)
or ratio much less than 1.0 M1
so good contrast A1 [2]

(*answer given in* **(c)(ii)** *must be consistent with ratio given in* **(c)(i)**)

© Cambridge International Examinations 2013

11 (a) (i) amplitude of the carrier wave varies M1
(in synchrony) with the displacement of the information signal A1 [2]

(ii) e.g. more than one radio station can operate in same region/less interference
enables shorter aerial
increased range/less power required/less attenuation
less distortion
(any two sensible answers, 1 each) B2 [2]

(b) (i) frequency = 909 kHz C1
wavelength = $(3.0 \times 10^8) / (909 \times 10^3)$
= 330 m A1 [2]

(ii) bandwidth = 18 kHz A1 [1]

(iii) frequency = 9000 Hz A1 [1]

12 (a) for received signal, $28 = 10 \lg(P / \{0.36 \times 10^{-6}\})$ C1
$P = 2.3 \times 10^{-4}$ W A1 [2]

(b) loss in fibre $= 10 \lg(\{9.8 \times 10^{-3}\} / \{2.27 \times 10^{-4}\})$ C1
= 16 dB A1 [2]

(c) attenuation per unit length = 16 / 85
= 0.19 dB km^{-1} A1 [1]

© Cambridge International Examinations 2013