Cambridge International AS & A Level

Cambridge International Examinations
Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS **9702/42**

Paper 4 A Level Structured Questions **May/June 2016**

MARK SCHEME

Maximum Mark: 100

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge will not enter into discussions about these mark schemes.

Cambridge is publishing the mark schemes for the May/June 2016 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is the registered trademark of Cambridge International Examinations.

© UCLES 2016

1 (a) (i) gravitational force provides/is the centripetal force — B1

same gravitational force (by Newton III) — B1 [2]

(ii) $\omega = 2\pi / T$
$= 2\pi / (4.0 \times 365 \times 24 \times 3600)$ — C1

$= 5.0\ (4.98) \times 10^{-8}\ \text{rad s}^{-1}$ — A1 [2]

(b) (i) (centripetal force =) $M_A d\omega^2 = M_B(2.8 \times 10^8 - d)\omega^2$
or
$M_A d_A = M_B d_B$ — C1

$M_A / M_B = 3.0 = (2.8 \times 10^8 - d) / d$ — C1

$d = 7.0 \times 10^7$ km — A1 [3]

(ii) $GM_A M_B / (2.8 \times 10^{11})^2 = M_A d\omega^2$ — B1

$M_B = (2.8 \times 10^{11})^2 \times d\omega^2 / G$
$= (2.8 \times 10^{11})^2 \times (7.0 \times 10^{10}) \times (4.98 \times 10^{-8})^2 / (6.67 \times 10^{-11})$ — C1

$= 2.0 \times 10^{29}$ kg — A1 [3]

2 (a) (i) number of atoms/nuclei in 12 g of carbon-12 — B1 [1]

(ii) amount of substance — M1

containing N_A (or 6.02×10^{23}) particles/molecules/atoms
or
which contains the same number of particles/atoms/molecules as there are atoms in 12 g of carbon-12 — A1 [2]

(b) $pV = nRT$

$2.0 \times 10^7 \times 1.8 \times 10^4 \times 10^{-6} = n \times 8.31 \times 290$, so $n = 149$ mol or 150 mol — A1 [1]

(c) (i) V and T constant and so pressure reduced by 5.0%
pressure $= 0.95 \times 2.0 \times 10^7$ — C1

or

calculation of new n (= 142.5 mol) and correct substitution into $pV = nRT$ — (C1)

pressure $= 1.9 \times 10^7$ Pa — A1 [2]

© Cambridge International Examinations 2016

(ii) loss is $5/100 \times 150\,\text{mol} = 7.5\,\text{mol}$
or
$\Delta N = 4.52 \times 10^{24}$ C1

$t = (7.5 \times 6.02 \times 10^{23})/1.5 \times 10^{19}$
or
$t = 4.52 \times 10^{24}/1.5 \times 10^{19}$ C1

$= 3.0 \times 10^{5}\,\text{s}$ A1 [3]

3 (a) no net energy transfer between the bodies
or
bodies are at the same temperature B1 [1]

(b) (i) thermocouple, platinum/metal resistance thermometer, pyrometer B1 [1]

(ii) thermistor, thermocouple B1 [1]

(c) (i) change = 11.5 K B1 [1]

(ii) final temperature = 311.2 K B1 [1]

4 (a) (i) $T = 0.60\,\text{s}$ and $\omega = 2\pi/T$ C1

$\omega = 10\,(10.47)\,\text{rad s}^{-1}$ A1 [2]

(ii) energy $= \frac{1}{2}m\omega^2 x_0^2$ or $\frac{1}{2}mv^2$ and $v = \omega x_0$ C1

$= \frac{1}{2} \times 120 \times 10^{-3} \times (10.5)^2 \times (2.0 \times 10^{-2})^2$

$= 2.6 \times 10^{-3}\,\text{J}$ A1 [2]

(b) sketch: smooth curve in correct directions B1

peak at f M1

amplitude never zero and line extends from $0.7f$ to $1.3f$ A1 [3]

(c) sketch: peaked line always below a peaked line A M1

peak not as sharp and at (or slightly less than) frequency of peak in line A A1 [2]

© Cambridge International Examinations 2016

5 **(a)** amplitude of the carrier wave varies M1

in synchrony with displacement of the information/audio signal A1 [2]

(b) **(i)** 10 kHz A1 [1]

(ii) 5 kHz A1 [1]

(c) **(i)** $24 = 10 \lg (P_{MIN} / \{5.0 \times 10^{-13}\})$ C1

$P_{MIN} = 1.3\ (1.26) \times 10^{-10}$ W A1 [2]

(ii) $45 \times 2 = 10 \lg (\{500 \times 10^{-3}\} / P)$

$P = 5.0 \times 10^{-10}$ (W) M1

$P > P_{MIN}$ so yes A1

or

maximum attenuation calculated to be 96 (dB) (M1)
96 dB > 2 × 45 dB so yes (A1)

or

maximum length of wire calculated to be 48 (km) (M1)
actual length 45 km < 48 km so yes (A1)

or

maximum attenuation per unit length calculated to be 2.2 dB km^{-1} (M1)
2.2 dB km^{-1} > 2.0 dB km^{-1} so yes (A1) [2]

6 **(a)** lines perpendicular to surface
or
lines are radial M1

lines <u>appear</u> to come from centre A1 [2]

(b) **(i)** $F_E = (1.6 \times 10^{-19})^2 / 4\pi\varepsilon_0 x^2$ C1

$F_G = G \times (1.67 \times 10^{-27})^2 / x^2$ C1

$F_E / F_G = (1.6 \times 10^{-19})^2 \times (8.99 \times 10^9) / [(1.67 \times 10^{-27})^2 \times (6.67 \times 10^{-11})]$
$= 1.2\ (1.24) \times 10^{36}$ A1 [3]

(ii) $F_E \gg F_G$ B1 [1]

© Cambridge International Examinations 2016

7 **(a)** e.g. storing energy
blocking d.c.
in oscillator circuits
in tuning circuits
in timing circuits

any two B2 [2]

(b) **(i)** $1/6 + 1/C + 1/C = 1/4$ C1

$C = 24\,\mu F$ A1 [2]

(ii) $Q = CV$
$= 4.0 \times 10^{-6} \times 12$ C1

$= 48\,\mu C$ A1 [2]

(iii) **1.** $48\,\mu C$ A1

2. $24\,\mu C$ A1 [2]

8 **(a)** **(i)** gain = <u>voltage</u> output / <u>voltage</u> input B1 [1]

(ii) changes in V_{OUT} M1
occur immediately when V_{IN} changes A1

or

changes in V_{IN} (M1)
result in immediate changes to V_{OUT} (A1) [2]

(b) $12 = 1 + R/(1.5 \times 10^3)$ C1

$R = 16.5\,k\Omega$ A1 [2]

(c) straight line from (0,0) to ($0.75t_1$, 9.0 V) B1

horizontal line from endpoint of straight line to t_1 B1

+9 V to –9 V (or *v.v.*) at t_1 B1

correct line to t_2 B1 [4]

© Cambridge International Examinations 2016

9	**(a)**	**(i)**	number density of charge carriers/<u>free</u> electrons *or* number per unit volume of charge carriers/<u>free</u> electrons	B1	[1]
		(ii)	PX or QY or RZ	B1	[1]
	(b)	**(i)**	V_H is inversely proportional to n	B1	
			for semiconductors, n is (much) smaller than for metals	B1	[2]
		(ii)	magnetic field would deflect holes and electrons in same direction	B1	
			(because) electrons are (–)ve, holes are (+)ve	M1	
			so V_H has opposite polarity/opposite sign	A1	[3]
10	**(a)**		iron rod changes flux (density)/field	B1	
			change of <u>flux</u> <u>in coil Q</u> causes induced e.m.f.	B1	[2]
	(b)		constant reading (either polarity) from time zero to near t_1	B1	
			spike in one direction near t_1 clearly showing a larger voltage	M1	
			of opposite polarity	A1	
			zero reading from near t_1 to t_2	B1	[4]
11	**(a)**		point P shown at 'lower end' of load	B1	[1]
	(b)		$V_{r.m.s.} = 6.0/\sqrt{2} = 4.24\,V$	C1	
			$I_{r.m.s.} = 4.24/(2.4 \times 10^3)$ $= 1.8 \times 10^{-3}\,A$	A1	[2]
	(c)	**(i)**	capacitor in parallel with load	B1	[1]
		(ii)	line from peak to curve at 3.0 V for either half- or full-wave rectified	M1	
			correct curvature on line (gradient becoming more shallow)	A1	
			line drawn as for full-wave rectified	A1	[3]

© Cambridge International Examinations 2016

12	**(a)**	**(i)**	(X–ray) <u>photon</u> produced when electron/charged particle is stopped/accelerated (suddenly)	B1	
			range of accelerations (in target)	M1	
			hence distribution of wavelengths	A1	[3]
		(ii)	electron gives all its energy to one photon	B1	
			electron stopped in single collision	B1	[2]
		(iii)	de-excitation of (orbital) electrons in target/anode/metal	B1	[1]
	(b)	**(i)**	aluminium sheet/filter/foil (placed in beam from tube)	B1	[1]
		(ii)	(long wavelength X-rays) do not pass through the body	B1	[1]
13	**(a)**		(photons of) electromagnetic radiation	M1	
			emitted from nuclei	A1	[2]
	(b)		line of best fit drawn	B1	
			recognises μ as given by the gradient of best-fit line *or* $\ln C = \ln C_0 - \mu x$	B1	
			$\mu = 0.061\,\text{mm}^{-1}$ (within $\pm 0.004\,\text{mm}^{-1}$, 1 mark; within $\pm 0.002\,\text{mm}^{-1}$, 2 marks)	A2	[4]
	(c)		aluminium is less absorbing (than lead) *or* gradient of graph would be less	M1	
			so μ is smaller	A1	[2]

© Cambridge International Examinations 2016