Cambridge International AS & A Level

Cambridge Assessment International Education
Cambridge International Advanced Subsidiary and Advanced Level

PHYSICS **9702/53**

Paper 5 Planning, Analysis and Evaluation **October/November 2017**

MARK SCHEME

Maximum Mark: 30

Published

This mark scheme is published as an aid to teachers and candidates, to indicate the requirements of the examination. It shows the basis on which Examiners were instructed to award marks. It does not indicate the details of the discussions that took place at an Examiners' meeting before marking began, which would have considered the acceptability of alternative answers.

Mark schemes should be read in conjunction with the question paper and the Principal Examiner Report for Teachers.

Cambridge International will not enter into discussions about these mark schemes.

Cambridge International is publishing the mark schemes for the October/November 2017 series for most Cambridge IGCSE®, Cambridge International A and AS Level components and some Cambridge O Level components.

® IGCSE is a registered trademark.

© UCLES 2017

Question	Answer	Marks
1	**Defining the problem**	
	d is the independent variable and *R* is the dependent variable **or** vary *d* and measure *R*	**1**
	keep intensity/power of light source constant	**1**
	Methods of data collection	
	labelled diagram showing a light source fixed above container of water with the labelled LDR positioned in the beaker	**1**
	correct circuit diagram to measure *R*, e.g. *V* and *I* methods or ohmmeter	**1**
	method to determine *R*, e.g. $R = \frac{\text{p.d. across LDR}}{\text{current}}$ or read off ohmmeter	**1**
	method to determine *d*, e.g. use a ruler or drawn labelled vertical ruler adjacent to container with *d* indicated	**1**
	Method of analysis	
	plots a graph of *R* against d^2	**1**
	relationship valid if a straight line produced passing through the origin	**1**
	$K = \frac{4\pi}{\text{gradient}}$	**1**

© UCLES 2017

Question	Answer	Marks
1	**Additional detail including safety considerations**	**Max. 6**
	D1 dark glasses to prevent damage to eyes due to light source **or** do not look directly at light source **or** do not touch hot lamp/use gloves to position hot lamp/heat-proof gloves to position lamp	
	D2 dark room or shielding LDR (so as to avoid light from other sources)	
	D3 use high intensity lamp or collimated beam or laser	
	D4 method described to check that current in light source is constant, e.g. use an ammeter and variable resistor / variable power supply	
	D5 keep position of light source constant or distance between light source and LDR constant	
	D6 light source is placed close to water surface to increase intensity/reduce reflections **or** light source is placed further away to make it more directional	
	D7 use tall container to give a wide range of d or R or to reduce uncertainties **or** use a wide container to reduce reflections	
	D8 method to position ruler vertically to measure d described e.g. use a set square/spirit level	
	D9 use of horizontal fiducial mark from ruler to meniscus or middle of LDR, e.g. pin **or** d = reading on rule at surface – reading at top of LDR	
	D10 ensure that the electrical connections/wire to the LDR are waterproof	

© UCLES 2017

<table>
<tr><th>Question</th><th>Answer</th><th>Marks</th></tr>
<tr><td>2(a)</td><td>gradient = $-\frac{2mg}{s}$

y-intercept = mg</td><td>1</td></tr>
<tr><td>2(b)</td><td><table><tr><td>$(T_1 - T_2)$ / N</td></tr><tr><td>5.5 ± 0.2</td></tr><tr><td>4.6 ± 0.2</td></tr><tr><td>3.6 ± 0.2</td></tr><tr><td>2.8 ± 0.2</td></tr><tr><td>1.9 ± 0.2</td></tr><tr><td>1.3 ± 0.2</td></tr></table>
First mark for column heading and values of $(T_1 - T_2)$ / N.

Second mark for all uncertainties = ± 0.2.</td><td>2</td></tr>
<tr><td rowspan="2">2(c)(i)</td><td>Six points plotted correctly.
Must be within half a small square. Diameter of points must be less than half a small square</td><td>1</td></tr>
<tr><td>Error bars in P plotted correctly.
All error bars to be plotted. Length of bar must be accurate to less than half a small square and symmetrical.</td><td>1</td></tr>
</table>

© UCLES 2017

Question	Answer	Marks
2(c)(ii)	Line of best fit drawn. Must not be drawn from top point to bottom point. If points are plotted correctly then upper end of line should pass between (0.125, 5.0) and (0.140, 5.0) **and** lower end of line should pass between (0.360, 1.5) and (0.380, 1.5).	**1**
	Worst acceptable line drawn correctly (steepest or shallowest possible line). All error bars must be plotted.	**1**
2(c)(iii)	Gradient determined with a triangle that is at least half the length of the drawn line. Must be negative.	**1**
	uncertainty = gradient of line of best fit – gradient of worst acceptable line **or** uncertainty = ½ (steepest worst line gradient – shallowest worst line gradient)	**1**
2(c)(iv)	*y*-intercept determined from substitution into $y = mx + c$.	**1**
	y-intercept determined using gradient of worst acceptable line. uncertainty = *y*-intercept of line of best fit – *y*-intercept of worst acceptable line **or** uncertainty = ½ (steepest worst line *y*-intercept – shallowest worst line *y*-intercept) No ECF from false origin method.	**1**

© UCLES 2017

Question	Answer	Marks
2(d)(i)	*m* determined using candidate's *y*-intercept **and** correct units for *m* and *s*. $m = \frac{y\text{-intercept}}{g} = \frac{y\text{-intercept}}{9.81}$	**1**
	s determined using candidate's gradient **and** *m* and *s* given to 2 or 3 significant figures. Correct substitution of numbers must be seen. $s = \frac{-2mg}{\text{gradient}} = \frac{-2 \times y\text{-intercept}}{\text{gradient}}$	**1**
2(d)(ii)	percentage uncertainty in *m* = percentage uncertainty in *y*-intercept	**1**
	percentage uncertainty in *s* = percentage uncertainty in gradient + percentage uncertainty in *y*-intercept **or** percentage uncertainty in *s* = percentage uncertainty in gradient + percentage uncertainty *m* Maximum/minimum methods: $\max s = \frac{-2 \times \max y\text{-intercept}}{\min \text{ gradient}}$ **or** $\frac{-2g \times \max m}{\min \text{ gradient}}$ $\min s = \frac{-2 \times \min y\text{-intercept}}{\max \text{ gradient}}$ **or** $\frac{-2g \times \min m}{\max \text{ gradient}}$ Correct substitution of numbers must be seen.	**1**

© UCLES 2017